

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

Claims 1 – 12: Cancelled

13. (currently amended) A seatbelt retractor for retracting a security belt windable and unwindable from a belt shaft that is rotatably supported in a housing, the seatbelt retractor comprising:

a tensioning drive that acts upon the belt shaft and that, upon triggering ~~release~~, rotates the belt shaft in a ~~the~~ wind up direction of the security belt, the tensioning drive including a first component that, upon release of the tensioning drive, initially initiates a rotation in a ~~the~~ pull out direction and a second component, the two components being set into movement relative to one another upon ~~the~~ triggering of the tensioning drive device ~~and~~ the tensioning drive device being arranged without a connection to the housing of the seatbelt retractor on the belt shaft and rotating in common, before the triggering of the seatbelt retractor, with the belt shaft;

a reverse movement stop is arranged between the first and second components of the tensioning drive; and

a blocking element that can be triggered in a belt-sensitive and/or vehicle-sensitive manner for blocking the rotation of the belt shaft in an ~~the~~ unwinding direction, the blocking element being retained on the first component and being, via the movement of the first component, steered into its blocking position, the belt shaft being connected with the second component of the tensioning drive, which second component is rotated in the wind up direction by reason of the application of a ~~the~~ drive force occurring in connection with the ~~fixedly disposed~~ first component that is fixedly disposed, wherein ~~whereby~~ the reverse movement stop is arranged between the first and second components of the tensioning drive

and is continuously effective in the extension direction and runs in a free running condition in the wind up direction.

14. (previously presented) A seatbelt retractor according to claim 13, wherein the reverse movement stop is configured as a ratchet stop with a latch that moves out of ratchet engagement with a tooth arrangement upon rotation in the wind up direction.

15. (withdrawn) A seatbelt retractor according to claim 13, wherein the tensioning drive is configured as an electro-motor whose stator forms the shaft body that acts as a support for the seatbelt in the role of the second component and whose rotor that retains the blocking element is in the role of the first component.

16. (withdrawn) A seatbelt retractor according to claim 13 and further comprising a force limiting device configured as a torsion bar, the torsion bar being arranged in the interior of the rotor and is connected on its one end in a form-fitting manner with a profile head serving as a support for the blocking element retained thereon and is connected on its opposite end in a form-fitting connection with the rotor, whereby the rotor is directly connected with the profile head via structures designed to give way at a preset force application.

17. (currently amended) A seatbelt retractor according to claim 13, wherein the tensioning drive is configured as a pyrotechnic drive with a housing connected to a shaft body supporting the belt in the role of the second component and with at least one drive piece arranged in the housing that is effective on a driveshaft ~~drive-shaft~~ acting in the role as a support for the blocking element and is flow-contacted by the gas produced from a gas generator upon the triggering of the tensioning drive in the role of the first component.

18. (previously presented) A seatbelt retractor according to claim 17, wherein the drive piece is configured as a piston that is flow-contacted by the gas.

19. (currently amended) A seatbelt retractor according to claim 18, wherein ~~the drive piece is configured from a piston that is flow-contacted by the gas, whereby, for the~~

purpose of a symmetrical force transmission in the event of a release, it can be provided that pistons are respectively arranged on both sides of the drive shaft in a symmetrical arrangement.

20. (previously presented) A seatbelt retractor according to claim 18, wherein the driveshaft and the piston are coupled with one another via meshing teeth in a manner such that the linear movement of the piston is, upon release of the tensioning drive, converted into a rotational movement of the driveshaft.

21. (currently amended) A seatbelt retractor according to claim 18, wherein a belt ~~there~~ is wound onto the driveshaft, ~~a belt~~ wherein the belt ~~that~~ is guided over the piston and is secured to the housing such that the linear piston movement leads to an unwinding of the belt from the driveshaft and, consequently, leads to a rotation of the housing relative to the ~~fixedly retained~~ driveshaft that is fixedly retained.

22. (withdrawn) A seatbelt retractor according to claim 17, wherein a belt is wound onto the driveshaft and a pre-curved chamber, disposed in the path of the flow of the gas, is closely disposed to the housing such that the flow-contacting of the belt leads to an unwinding of the belt from the driveshaft and, consequently, a rotation of the housing relative to the fixedly set driveshaft.

23. (currently amended) A seatbelt retractor according to claim 17 and further comprising a force limiting device configured as an inner disposed torsion bar that is driven by the piston at its end arranged relative to the tensioning drive and is connected at its opposite end with a profile head serving as a support of the blocking element, wherein ~~whereby~~ the shaft body is connected with the profile head via structures designed to give way at a preset force application.

24. (previously presented) A seatbelt retractor according to according to claim 17 and further comprising a gas generator arranged on a fixedly set cover of the seatbelt

Appl. No. 10/523,472
Amdt. Dated January 24, 2008
Reply to Office Action of September 24, 2007

retractor and extends with its gas exhaust region into a partitioned gas space configured in the housing of the tensioning drive.